

Technical Information Melcourt Equichips® - FSC

Product Description

A clean, lightweight graded woodchip suitable for training gallops, arenas, recovery yards, bridle paths, horse walkers and heavily used crossings

- Nominal particle size range of 5 - 40mm
- Free from fines and dust, providing excellent drainage
- Produced from sustainably managed British forests
- Certified under the Forest Stewardship Council (FSC)
- Hard-wearing with an excellent durability of 3 to 5 years plus
- Pale beige in colour darkening to a deep grey brown with time
- Sold in loose bulk

User Benefits

- Easy to install
- Long effective service life
- Remains serviceable at freezing temperatures
- High resistance to wear
- Wind firm
- Very cost effective
- Permits clean access onto surface for horses and maintenance equipment
- Simple low cost maintenance to keep surface in peak condition with no specialist equipment necessary
- An all-weather training surface
- Can be used under a top surface of Melcourt Equifibre where added firmness is required in a training gallop and manege or where a high percentage of jumping is likely

How to Use

Instructions on correct installation and after care can be found on our website at www.melcourt.co.uk.



Contact

Melcourt Industries Limited, Boldridge Brake, Long Newnton, Tetbury, Gloucestershire. GL8 8RT
 Tel: +44 (0)1666 502711 Fax: +44 (0)1666 504398 Email: mail@melcourt.co.uk
 Web Site: www.melcourt.co.uk

Melcourt Equichips® - FSC

The following table gives a guide to the area, in square metres, covered by one cubic metre, when evenly laid at the given depths:

Melcourt Equichips® depth required	300 mm	250 mm	200 mm	150 mm	100 mm
Coverage in Sq. Metres	3.3	4.0	5.0	6.6	10.0

Melcourt Equichips® is free flowing and will settle during initial rolling. Approximately 10% compaction should be allowed when calculating the final finished depth to be installed.

Product settlement percentages are provided for your guidance only. If the product settles more than the minimum figure stated, it is the customer's responsibility to order sufficient additional material, to give the required finished depth.

TECHNICAL SPECIFICATION

Main Constituent	Origin	Nominal particle size range	Wood content	Dust & fines
Wood	British	5 - 40 mm	90 % +	Minimal

Typical Bulk Density Range	Quality range	Installation depth	Settlement factor	Durability	FSC Certified
260 - 310 kg/m ³	Deluxe	125 - 250 mm	10% +	3 - 5 years +	Yes

All values given in the Technical Specification are typical. However, some variation may occur from time to time. Melcourt Industries Ltd reserves the right to alter the specification without notice, for the purpose of product improvement.