

Technical Information Melcourt Pine Mini Mulch™

Product Description

A neat, small chip, high performance mulch, from our 'deluxe' range, suitable for a wide range of mulching applications, particularly on smaller beds and borders or tubs, pots, window boxes and roof gardens

- Particles in the range 3 - 18mm
- Naturally acidic
- Free flowing and easy to handle
- Very attractive appearance
- Rich mid-brown in colour
- Effective service life of 2 years plus
- Processed from natural, sustainably produced pine bark
- Hostile living environment for pests
- 100% peat free
- Sold in 75 litre bags, bulk bags and in loose bulk

User Benefits

- Suppresses weed growth replacing expensive shrub bed hoeing and chemical weed-killing
- Conserves soil moisture, minimising drought stress and plant death and eliminating the need for excessive plant watering
- Substantially enhances the visual appearance of new and existing planted areas
- Successfully used for many years on sites throughout the UK and proved to perform extremely well
- Provides an insulating layer, substantially reducing the effects of ground freezing and over-heating during extreme weather conditions
- Slowly improves the soil's organic content, as it decomposes into the soil
- Easy to lay and install, using simple tools and requiring little subsequent maintenance
- Allows clean access onto mulched area for plant pruning



How to Use

- Ensure the area to be mulched is entirely free from both annual and perennial weeds
- Lay Melcourt Mini Mulch™ evenly onto freshly cultivated moist soil, after planting has been completed.
- The mulch should be laid at between 50 to 100mm depths, allowing at least 5% for settlement
- For greatest longevity, do not disturb once applied
- When used in tubs, pots and window boxes, spread to a minimum depth of 50mm, onto moist soil or compost. As the mulch will remain loose, ensure that there is a sufficient depth of rim to contain the bark.



Contact

Melcourt Industries Limited, Boldridge Brake, Long Newnton, Tetbury, Gloucestershire. GL8 8RT
 Tel: +44 (0)1666 502711 Fax: +44 (0)1666 504398 Email: mail@melcourt.co.uk
 Web Site: www.melcourt.co.uk

Melcourt Pine Mini Mulch™

The following text is recommended to be used by landscape architects and product specifiers, when inviting quotations for this product. The use of this text will not contravene the copyright of this publication.

“

Product Specification

- The product shall consist of predominantly matured European Pine Bark with an even nominal particle size distribution of 3-18 mm with minimal dust and fines and less than 5% wood content.
- The pH to be between 4.5 and 5.5.
- The product shall be pest, disease and weed free and not have been treated with Methyl Bromide or any additives.

Process Specification

- The natural heat treatment maturing process shall have been sufficient to ensure that excess volatile substances are driven from the product.
- During the process, temperatures within the product heaps must exceed 50°C for a minimum 14 day period, followed by a further period of stabilization.

Application Rates

- Lay Melcourt Pine Mini Mulch™ to a finished depth of mm (*insert finished depth required*) allowing at least 5% for settlement after 30 days.

Additional Clauses

- Typical product samples to be provided upon request.
- All product volumes to be calculated using The Bulk Density method, as set out in BS EN 12579:2000 and BS EN 12580:2000.

Available from

Melcourt Industries Limited
 Boldridge Brake, Long Newnton,
 Tetbury, Glos GL8 8RT
 Tel: +44 (0)1666 502711
 Fax: +44 (0)1666 504398
 Email: mail@melcourt.co.uk
 Website: <http://www.melcourt.co.uk>

”

The following table gives a guide to the area in square metres, covered by one cubic metre, when evenly laid at the given depths:

| Mulch depth required | 50 mm | 75 mm | 100 mm |
|---|-------|-------|--------|
| Square metres covered by 1 cubic metre of mulch | 20 | 13.3 | 10 |

A suitable allowance for settlement should be made, as stated in 'How to Use', above.

Product settlement percentages are provided for your guidance only. If the product settles more than the minimum figure stated, it is the customer's responsibility to order sufficient additional material, to give the required finished depth.

TECHNICAL SPECIFICATION

| Main Constituent | Origin | Nominal particle size range | Wood content | Dust & fines | pH |
|------------------|----------|-----------------------------|--------------|--------------|-----------|
| Pine Bark | European | 3 - 18 mm | <5 % | Minimal | 4.5 - 5.5 |

| Typical Bulk Density Range | Quality range | Minimum effective depth | Settlement factor | Durability | BS 4790 Fire Tested |
|-----------------------------|---------------|-------------------------|-------------------|------------|---------------------|
| 250 - 320 kg/m ³ | Deluxe | 50 mm | 5 - 10% | 2 years + | No |

All values given in the Technical Specification are typical. However, some variation may occur from time to time. Melcourt Industries Ltd reserves the right to alter the specification without notice, for the purpose of product improvement.