

Melcourt Equestrian Surfaces Product Technical Specification Guide

	Melcourt Equichips®	Melcourt Equifibre™
1. Main constituent	Wood	Wood
2. Origin	British	British
3. Nominal particle size range	5 - 40 mm	3 - 30 mm
4. Wood content	> 90 %	> 90 %
5. Dust & fines	Minimal	Minimal
6. Installation Depth	125 - 250 mm	250 - 300 mm
7. Typical Bulk Density Range	260 - 310 kg/m ³	250 - 300 kg/m ³
8. Settlement factor	10% +	15%
9. Durability	3 - 5 years +	2 - 4 years +
10. FSC Certified	Yes	No
11. Quality Range	Deluxe	Deluxe



Contact

Melcourt Industries Limited, Boldridge Brake, Long Newnton, Tetbury, Gloucestershire. GL8 8RT
 Tel: +44 (0)1666 502711 Fax: +44 (0)1666 504398 Email: mail@melcourt.co.uk
 Web Site: www.melcourt.co.uk

Melcourt Equestrian Surfaces Product Technical Specification Guide

NOTES

Lines 3,4 and 5 The sizes and percentages (by weight) are nominal. By the nature of these products, it is not practically possible to be exact and there might be a small variation.

Line 5 "Dust and Fines" refers to particles less than 1 mm in diameter.

All values given in the Product Specification are typical. However, some variation may occur from time to time. Melcourt Industries Ltd reserves the right to alter the specification without notice, for the purpose of product improvement.



Contact

Melcourt Industries Limited, Boldridge Brake, Long Newnton, Tetbury, Gloucestershire. GL8 8RT
Tel: +44 (0)1666 502711 Fax: +44 (0)1666 504398 Email: mail@melcourt.co.uk
Web Site: www.melcourt.co.uk