



Melcourt Play Product Specification and Performance Guide

	<u>Melcourt Playbark® 10/50</u>	<u>Melcourt Playbark® 8/25</u>	<u>Melcourt Playchips®</u>	<u>Melcourt Kushyfall®</u>	<u>Melcourt Softfall™</u>	<u>Melcourt Playsand™</u>
1. Main constituent	Pine Bark	Pine Bark	Wood	Wood	Wood	Silica sand
2. Origin	European	European	British	British	British	British
3. Nominal particle size range	10 - 50 mm	8 - 25 mm	5 - 40 mm	3 - 30 mm	1 - 100 mm	0.25 - 0.45 mm
4. Wood content	< 2.5 %	< 2.5 %	> 85 %	> 95 %	> 70 %	0 %
5. Dust & fines	Minimal	Minimal	Minimal	Minimal	< 15 %	nr
6. Typical Bulk Density Range	210 - 260 kg/m ³	210 - 260 kg/m ³	260 - 310 kg/m ³	250 - 300 kg/m ³	80 - 130 kg/m ³	1500 kg/m ³
7. Quality range	Deluxe	Deluxe	Deluxe	Contract	Economy	Deluxe
8. Settlement factor	10 % +	10 % +	10 % +	15 % +	20 % +	< 5 %
9. Durability	4 - 6 years	3 - 5 years	2 - 4 years	2 - 4 years	2 - 3 years	6 - 8 years
10. BS EN 1176 compliance	Yes	Yes	Yes	Yes	Yes	Yes
11. BS EN 1176 CFH tested at 100mm, 200mm and 300mm depths	Yes	Yes	Yes	Yes	Yes	Yes
12. BS 4790:1987 Fire tested	Yes	Yes	Yes	Yes	Yes	100 % resistant
13. Resistance to fire	****	***	***	***	**	*****
14. FSC Certified	No	No	Yes	No	No	No
15. Porosity to rain	*****	****	****	***	***	***
16. Porosity to air	*****	****	****	**	**	**
17. Resistance to rain erosion	*****	****	****	***	***	***
18. Resistance to wind erosion	****	***	***	**	**	**
19. Stability on slopes	Up to 30°	Up to 25°	Up to 20°	Up to 20°	Up to 20°	Up to 5°
20. Insulation properties	****	***	***	***	***	***
21. Consistency of product	*****	*****	****	****	***	*****

Contact

Melcourt Industries Limited, Boldridge Brake, Long Newnton, Tetbury, Gloucestershire. GL8 8RT
 Tel: +44 (0)1666 502711 Fax: +44 (0)1666 504398 Email: mail@melcourt.co.uk
 Web Site: www.melcourt.co.uk

Melcourt Play Product Specification and Performance Guide

Notes

- Lines 3,4 and 5** The sizes and percentages are nominal. By the nature of these products, it is not possible to be exact and there might be a small variation.
- Line 7** Melcourt products are classified in 'deluxe', 'contract' and 'economy' product ranges.
- Line 8** This is the likely reduction in product depth, 30 days after installation.
- Line 9** These figures are taken from our practical experience over many years. Life expectancy of LIAS will depend on the initial installation depth, subsequent topping up and maintenance; together with the number of children using the play facility.
- Line 10** These products comply with the examples of product specification, as set out in EN 1176 Table A.1
- Line 11** These products have been independently tested by BSI Testing or The Centre for Sports Technology in accordance with the requirements of BS EN1176 at depths of 300mm, 200mm and 100mm.
- Line 12** These products have been independently tested by WIRA Testing Centre, for fire resistance, in accordance with the requirements of BS 4790:1987.
- Lines 14-20**
- | | |
|------------|-----------|
| Key | |
| ***** | Very good |
| **** | Good |
| *** | Moderate |
| ** | Poor |
| * | Very poor |

All values given in the Product Specification are typical. However, some variation may occur from time to time. Melcourt Industries Ltd reserves the right to alter the specification without notice, for the purpose of product improvement.



Contact

Melcourt Industries Limited, Boldridge Brake, Long Newnton, Tetbury, Gloucestershire. GL8 8RT
 Tel: +44 (0)1666 502711 Fax: +44 (0)1666 504398 Email: mail@melcourt.co.uk
 Web Site: www.melcourt.co.uk