



Melcourt Walk Surfaces Product Specification and Performance Guide

	<u>Melcourt Walk Chips</u>	<u>Melcourt Woodfibre</u>
1. Main constituent	Wood	Conifer Fibre
2. Origin	British	British
3. Nominal particle size range	10 - 50 mm	1 - 30 mm
4. Wood content	> 85 %	> 95 %
5. Dust & fines	Minimal	< 15 %
6. pH	5.5 – 6.5	5.5 – 6.5
7. Typical Bulk Density Range	260 -310 kg/m ³	250 - 300 kg/m ³
8. Minimum effective depth	70 mm	100 mm
9. Settlement factor	10 - 15 %	20 - 25 %
10. Durability	4 years +	3 years +
11. BS 4790:1987 Fire tested	No	No
12. FSC Certified	Yes	No
13. Porosity to rain	***	**
14. Porosity to air	****	**
15. Resistance to rain erosion	***	**
16. Resistance to wind erosion	****	**
17. Resistance to fire	***	***
18. Stability on slopes	Up to 30°	Up to 20°
19. Insulation properties	***	***
20. Consistency of product	***	****

Contact

Melcourt Industries Limited, Boldridge Brake, Long Newnton, Tetbury, Gloucestershire. GL8 8RT
 Tel: +44 (0)1666 502711 Fax: +44 (0)1666 504398 Email: mail@melcourt.co.uk
 Web Site: www.melcourt.co.uk

Melcourt Walk Surfaces Product Specification and Performance Guide

Notes

- Lines 3,4 and 5 The sizes and percentages(by weight) are nominal. By the nature of these products, it is not possible to be exact and there might be a small variation.
- Line 6 pH is measured using the BS EN method
- Line 8 This is the minimum effective spreading depth after settlement for the product to function adequately. For improved effect, the depth could be increased.
- Line 9 This is the minimum reduction in product depth 30 days after laying.
- Line 10 These figures are taken from our practical experience. The life expectancy of all walk surfaces depends on the grade, the original spreading depth prior soil preparation, and subsequent topping-up and maintenance together with frequency of use.
- Line 12 These products are from FSC Mixed Sources at a minimum of 50%, FSC certificate number CU-COC-806457.
- Lines 13-20 **Key**
 ***** Very good
 **** Good
 *** Moderate
 ** Poor
 * Very poor

All values given in the Product Specification are typical. However, some variation may occur from time to time. Melcourt Industries Ltd reserves the right to alter the specification without notice, for the purpose of product improvement.



Contact

Melcourt Industries Limited, Boldridge Brake, Long Newnton, Tetbury, Gloucestershire. GL8 8RT
 Tel: +44 (0)1666 502711 Fax: +44 (0)1666 504398 Email: mail@melcourt.co.uk
 Web Site: www.melcourt.co.uk